# LIQUID LIGHTNING PRO

### **Material Safety Data Sheet**

Chem Trec Emergency 800-424-9300

**Product Name:** 

Sulfuric Acid (H2SO4)

CAS Number:

Synonyms:

7664-93-9 Sulphuric Acid; Oil of Vitriol; Dipping Acid; Vitriol

Brown Oil; Hydrogen Sulfate

**DOT Shipping Description:** 

Sulfuric Acid, 8, UN 1830, PGII, RQ

# Hazards Identification / Health Hazard Data

**Hazard Communication Status:** 

Corrosive

**Hazardous Components:** 

**Acute Health Effects:** 

Sulfuric Acid 93.2%

General - Reacts with all body tissue and eyes to produce

severe burns and/or blindness.

Inhalation - Exposure to mists may cause irritation of nose,

throat and lungs, cough, headache, nausea, weakness.

Symptoms may be delayed.

Ingestion - Harmful or Fatal if swallowed. Product will severely burn the digestive tract. Damage may appear days

after exposure.

**Chronic Health Effects:** 

Inhalation - Repeated exposure may cause severe shortness

of breath, chronic bronchitis, chronic inflammation of the nose

and throat, corrosion/discoloration of teeth.

Skin Contact - Repeated exposure to mist or low

concentrated liquid may cause dermatitis.

**Hazards Information:** 

**TSCA Inventory Status:** 

Yes

SARA Extremely Hazardous Substance: Yes

Yes

Acute: Chronic: Yes

**CERLCA Hazardous Substance:** 

No

Fire:

No

**SARA Toxic Chemical:** 

None

Reactivity: Yes Pressure: No

Carcinogens:

Health Flammability NFPA NPCA-HMIS 3

0

Reactivity

First Aid Eye or Skin Contact:

Immediately flush with water for at least 15 minutes, while

3

0

removing contaminated clothing. Get medical attention immediately. Apply cold, wet compresses; repeat flushing

with cold water.

Inhalation:

Remove from exposed area to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention immediately.

Ingestion:

**DO NOT** induce vomiting. If conscious, give large quantities

of water. Get medical attention immediately.

#### Fire and Explosion Hazard Data

Flash Point:

Non flammable.

**Extinguishing Media:** 

Dry chemical or carbon dioxide. Water reacts violently with

concentrated acid giving off heat.

**Special Fire Fighting Procedures:** 

Generates heat upon addition of water, with possible

splattering. Wear self-contained breathing apparatus and full protective clothing. Thoroughly decontaminate equipment

after use.

**Unusual Fire and Explosion Hazard:** 

Will react with most metals, especially when dilute, to produce explosive Hydrogen gas. Will react with organic materials with evolution of heat and sulfur dioxide.

#### V. Storage and Handling

Handling:

Employees must be properly trained to handle sulfuric acid. Avoid breathing vapors or mist. Do not add water to contents. Do not smoke in a sulfuric acid storage area. Use nonsparking tools and vapor-proof type electrical fixtures.

Storage:

Keep out of sun and away from heat sparks and flame. Keep away from incompatible material. Storage tanks must be ventilated. Do not add water to concentrated acid.

#### Accidental Release Measures/Waste Disposal

Spills:

Keep people away. Prevent contact with skin. Wear full protective equipment when handling sulfuric acid. Keep combustibles away from spilled material. Dike flow of spilled material with sand, gravel or whatever is available. Contact appropriate Federal, State or local officials. After obtaining approval from Federal, State or local officials, neutralize spill with soda ash or lime to a pH of 7. Prevent liquid from

entering sewers or waterways.

Disposal:

Follow Federal, State and local regulations for disposal. Make sure spilled material is neutralized to a pH of 7 and disposed of in an approved site. If not diluted and neutralized, this waste would be a hazardous waste (RCRA

Hazardous Waste No. D002-Corrosive) as designated in 40 CFR 261. Reportable quantity is 1,000 pounds (based on

sulfuric acid content.)

#### VII. Applicable Control Measures

**Engineering Controls:** 

General ventilation must be provided.

**Personal Protective Equipment:** 

**Eye Protection:** 

Wear chemical safety goggles. Have eye bath and safety

shower immediately available.

**Skin Protection:** 

Wear full length face shield/chemical splash goggles

combination, acid-proof gauntlet gloves, apron and boots, long-sleeved wool, acrylic or polyester clothing, acid-proof

suit and hood.

**Respiratory Protection:** 

Use NIOSH approved equipment with full-face piece when

airborne exposure limits are exceeded.

**Exposure Limits:** 

1 mg/m3, 8 Hr. TWA PEL (OSHA):

TLV (ACGIH): 1 mg/m3.8 Hr. TWA, A2 STEL 3 mg.m3, A2

## VIII. Typical Physical Properties

Appearance:

Colorless, oily liquid

Odor:

None

**Boiling Point:** 

535°F (279°C)

Solubility in water: Completely miscible

**Melting Point:** 

-31°F (-35° C)

pH:

1.835

Vapor Pressure:

< 0.6 mm Hg @ 100°F < 0.3 mm Hg @ 77°F

Specific Gravity: Vapor Density:

3.4

#### Reactivity Data

**Chemical Stability:** 

Product is stable but reacts violently with water and organic

materials with evolution of heat.

**Hazardous Polymerization:** 

Will not occur.

Incompatibility:

Vigorous reactions with water, alkaline solutions, metals, metal powder, carbides, chlorates, fuminates, nitrates, picrates,

combustible organic materials.

**Hazardous Decomposition Products:** 

Hazardous gases evolve on contact with cyanides, sulfides, carbides. Hydrogen gas (highly flammable/explosive limits 4-75% by volume) is generated by the action of sulfuric acid on

most metals.

**Decomposition:** 

Releases sulfur dioxide at extremely high temperatures.

#### **Transportation Information**

**Proper Shipping Name:** 

Sulfuric Acid

**Hazardous Class:** 

8

**DOT Label:** 

Corrosive

Reportable Quantity: 1000 Pounds

**UN Number:** 

1830

Packing Group:

This information is for the specific material described only and may not be valid if the material is used in combination with any other materials or in any process. The user is responsible to determine the completeness of the information and suitability for the user's own particular use. To the knowledge and belief of GAC Chemical Corporation, the information is accurate and reliable as of the date indicated, but GAC Chemical Corporation makes no express or implied warranty of merchantability for the material or for the information. GAC Chemical Corporation makes no express or implied warranty of fitness for a purpose for the material or for the information.